



TurfFan P1

Product Specifications

" Dedicated Air Movement Fan for grass "

Stadium design is dictating an enhanced experience for the sports fan. This means that stadiums are being constructed with higher sides, roofs, less natural light and as a result poor natural air circulation. Turfgrass at the canopy level should have approximately 3 m/s of air movement to enhance growth and reduce the instance of disease.

The P1 TurfFan is a dedicated air movement fan. The fan is grass specified with standard features after listening to what our customers Grounds managers and Ground persons require along with 40 years of engineering excellence





"They are the difference maker between healthy and stressed out turf"



SeeGrow TurfFans are pre-wired and pre-assembled for easier installation. They come complete with a ground sleeve, a fan pole, an oscillation assembly and a power control package. The power control package includes multiple modes of operation (fan blade on/off, oscillation on/off, and an optional electronic starter contact for remote use through an irrigation signal) with overload protection.

info@seegrow-grass.com + 44 (0) 1483 941 205 www.seegrow-grass.com SeeGrow® is a registered trademark of Linde Gas Bridge Farm, Knowle Lane Cranleigh, Surrey GU6 8JW Company Registration No. 8185087, Vat No. 141154844







TurfFan P1

Product Specifications

SeeGrow TurfFan P1 standard features

All Aluminium Housing & Internal Inlet Bell > Increases Velocity and no rust Powder Coated Finish > Keeps Fan Looking New Heavy Duty Anti-Vibration Mount > Less Noise Pivoting Tilt System > Air Flow Matches Green Slope or pitch Completely Pre-Wired > No Additional Electrical Costs Fan speed control 7 Day Multi function Timer Multi-Function Control Switch > Off/On/Oscillation/Irrigation Signal Enclosed Oscillating Motor > Added Weather/ Sprinkler Protection Heavy Duty Oscillating Gear Motor > Long Trouble Free Life High-Efficiency Baldor Fan Motor > Long Life Dependability Corrosion Free Composite - Adjustable Fan Blade Long Throw, Quiet Operation Rubber Mounted Guards > Reduces Noise, Increases Safety Delivered Fully Assembled > Quick and Easy Set Up Thermal Overload Protection > Protects Motor Burnout One Year Warranty

Oscillating Coverage: 140 degrees

Precision 50" Premium Fans					Output			
Baldor High Efficiency Motor							Sound Level	
HP		Phase	Volts	Amps	CFM/ CMM			
5		3	415	6.7	46,200 -1309	48		



SeeGrow® is a registered trademark of Linde Gas Bridge Farm, Knowle Lane Cranleigh, Surrey GU6 8JW Company Registration No. 8185087, Vat No. 141154844

